

First Aid Cupboard Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Shelves Supplied</u>
1800mm	1200mm	460mm	3
1800mm	900mm	460mm	3
900mm	460mm	460mm	1
900mm	900mm	460mm	1
700mm	350mm	300mm	1
700mm	900mm	460mm	1
(Mobile Cupboard) 1040mm	900mm	460mm	1
(Mobile Cupboard) 840mm	900mm	460mm	1
(Wall Mounted) 570mm	850mm	255mm	1

Cupboard Construction:

- 0.7mm mild steel, pop riveted carcass construction
- Rust resisting galvanised shelves
- Door aperture has return bends to eliminate open gaps
- Delivered assembled
- Reaction to Fire Classification EN 13501-1 – documents available
- Supplied with two first aid stickers
- 2-point locking mechanism
- Extra shelves and stands are available with the First Aid Cupboard range

Cupboard Door Construction:

Material: 0.9mm Mild Steel. A stiffener is spot welded vertically in the centre of the door with two 2.½” butt hinges spot welded to the door. The door is attached to the carcass via the hinges, with 4.8mm pop rivets. The door has two-point locking with an all metal key locking handle.

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Carcass powder coated with a special paint – **White BS 00.E.55**

Carcass & Door colour:

White	BS 00.E.55
-------	------------

Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)



RICHARDSONS
MAKING WORKSPACE WORK

6 Collingwood Court
Riverside Park
Middlesbrough TS2 1RP

Tel: 01642 242228 | Fax: 01642 242259

www.richardsonsuk.co.uk | sales@richardsonsuk.co.uk